

OIL APPLICATIONS

Impregnating oil :

Natural impregnating oil for wooden floor, panelling, stairways, decorative mouldings, furniture... (11 species). Available in 1 and 5 liter.

Satin finishing oil

Natural satin finishing oil for wooden floor, paneling, stairways, decorative mouldings, furniture... (this product must be used after applying impregnating oil). Available in 1 and 5 liter.

APPLICATION

The application must be done on a clean and well-sanded surface. Note that the sanding could affect the degree to which the oils are absorbed as well as the color of wood species. Following sanding the floor, protect it from any possible contaminates as: foot-prints, grease, drops of water ...)

Applying coat penetrating oil (neutral or colored)

Apply a thin coat of the impregnating oil using a clean cloth. It is suggested to work by section, to avoid oil from drying too fast. It is important to remove excess oil with a cloth. Allow oil to dry 24 hours prior to applying the finishing oil.

Application of satin finishing oil

24 hours following the application of the impregnating oil, proceed with the application of the finishing oil using the same method as the application of the impregnating oil.

One to two hours following the application, use the monobrush machine with white pad to give brightness to your floor.

Useful tips

Following the application of the finishing oil, avoid washing the floor for a period of 21 days. It is strongly recommended to clean your floor with water using Dergos soap. It is strongly recommended to test a small section of the floor prior to oiling the entire surface.